

Standard Treatment Plant for 15 to 25 people



Uni:15

Dimensions

Tank Height	2690mm
Tank Width	1370mm
Tank Length	3810mm
Invert Level Inlet	640mm
Invert Level Outlet	740mm

Compressor Blower	internal
Power Consumption	280w
Treatment Capacity	10872 litres
Effluent Quality	20:30:20
Design Hydraulic Flow	3000 litres (0.9kg / day)
Gravity System	standard
Desludging Interval (full loading)	60 – 90 days
Weight empty (approx.)	995kg

Uni:18

Dimensions – see above specification for Uni:15

Compressor Blower	internal
Power Consumption	280w
Treatment Capacity	10872 litres
Effluent Quality	20:30:20
Design Hydraulic Flow	3600 litres (1.08kg / day)
Gravity System	standard
Desludging Interval (full loading)	60 - 90 days
Weight Empty (approx.)	1000kg

Uni:25

Dimensions – see above specification for Uni:15

Compressor Blower	internal
Power Consumption	280w
Treatment Capacity	10872 litres
Effluent Quality	20:30:20
Design Hydraulic Flow	5000 litres (1.5kg / day)
Gravity System	standard
Desludging Interval (full loading)	60 – 90 days
Weight empty (approx.)	1000kg